Product Cut Sheet

DOUBLE-SIDED WIDE VERTICAL CABLING SECTIONS

These space-saving ducts, with locking latches, hold and separate wiring for a more organized and managed equipment room installation. Provides convenient cable run between equipment racks. Conceals cable for a more attractive installation. 2.50" (63.5 mm) diameter ports spaced at 11.625" (295.28 mm) intervals allow for convenient cable and wiring pass through. Vertical slots secure optional Saf-T-Grip® Cable Management Straps for neatly bundled cables.

- Bolts to CPI Standard Rack, Universal Rack, QuadraRack 4-Post Frame and QuadraRack Server Frame
- Includes formed cabling section, lockable cabling latches 12" (300 mm) between latches, protective edge guards and mounting hardware
- 6"W x 12.75"D (150 mm x 323.9 mm); double-sided cable trough
- 2.5" (64.0 mm) diameter pass through ports every 11.62" (295.1 mm)
- 9' (2.7 m) version consists of a 7' (2.1 m) section with a 2' (0.6 m) extension
- . Mounting hardware included

	Part Number	Description ft (m)	Shipping Weight Ib (kg)
ı	11729-X03	7 (2.1) Double-Sided Wide	30 (13.6)
ı	11729-X15	8 (2.4) Double-Sided Wide	31 (14.1)
ı	11729-X08	9 (2.7) Double-Sided Wide	32 (14.5)


X=color: 1=Gray, 2=Computer Beige, 5=Clear, 7=Black, E=Glacier White.

Double-Sided Wide Vertical Cabling Section Extensions

Adds one or two feet of height to vertical cabling sections, providing a uniform vertical pathway from ceiling to rack. Mounting hardware included.

Part Number	Description W x D in (mm)	Shipping Weight Ib (kg)
11781-X01	One-Foot Extension 6 x 12.75 (150 x 323.9)	5 (2.3)
11782-X01	Two-Foot Extension 6 x 12.75 (150 x 323.9)	9 (4.1)

X=color: 1=Gray, 2=Computer Beige, 5=Clear, 7=Black, E=Glacier White.



11729-503 Double-Sided Wide

