

# Product Cut Sheet

## FIXED WALL-MOUNT EQUIPMENT RACK

The Fixed Wall-Mount Equipment Rack is a sturdy platform for wall mounting equipment.

- EIA-310-D compliant equipment mounting system, punched with the Universal alternating 5/8"-5/8"-1/2" (15.9 mm -15.9 mm -12.7 mm) hole pattern
- Rack-mount spaces are marked and numbered, tapped with #12-24 roll-formed threads
- Includes (50) #12-24 equipment mounting screws. Black painted racks ship with black screws; other racks ship with zinc screws
- Supports single-sided and double-sided shelves
- Supports 200 lb (90.7 kg) of equipment when securely mounted to wall or backboard using all eight leg mounting holes



### Wall-Mount Rack Accessory

Attached to the Fixed Wall-Mount Rack. Creates a pathway from the wall to the front, side or rear of the equipment mounting space.

- Made from a polymer-blend material that is UL Rated for use in plenum spaces
- Flexible material holds bundles secure while also allowing easy entrance of additional cables
- Internal Diameter: 3" (80 mm)
- Finish: Black
- Kit includes 6 rings and mounting hardware



| Part Number | Part Number           | Shipping Weight lb (kg) |
|-------------|-----------------------|-------------------------|
| 11799-001   | Set of 6 Rings, Black | 2 (0.9)                 |

| Fixed Wall-Mount Equipment Rack |                   |        |          |                        |            |            |                         |
|---------------------------------|-------------------|--------|----------|------------------------|------------|------------|-------------------------|
| Part Number                     | Usable Dimensions |        |          | Overall Dims - in (mm) |            |            | Shipping Weight lb (kg) |
|                                 | Height            | Width  | Depth    | Height                 | Width      | Depth      |                         |
| 11960-X06                       | 13U               | 19"EIA | 6 (150)  | 27.4 (696)             | 22.4 (569) | 6.6 (168)  | 9 (4.1)                 |
| 11960-X12                       | 13U               | 19"EIA | 12 (300) | 27.4 (696)             | 22.4 (569) | 12.6 (320) | 12 (5.4)                |
| 11960-X18                       | 13U               | 19"EIA | 18 (457) | 27.4 (696)             | 22.4 (569) | 18.6 (472) | 13 (5.9)                |
| 11961-X06                       | 21U               | 19"EIA | 6 (150)  | 41.4 (1052)            | 22.4 (569) | 6.6 (168)  | 10 (4.5)                |
| 11961-X12                       | 21U               | 19"EIA | 12 (300) | 41.4 (1052)            | 22.4 (569) | 12.6 (320) | 13 (5.9)                |
| 11961-X18                       | 21U               | 19"EIA | 18 (457) | 41.4 (1052)            | 22.4 (569) | 18.6 (472) | 15 (6.8)                |
| 11962-X06                       | 41U               | 19"EIA | 6 (150)  | 76.4 (1941)            | 22.4 (569) | 6.6 (168)  | 15 (6.8)                |
| 11962-X12                       | 41U               | 19"EIA | 12 (300) | 76.4 (1941)            | 22.4 (569) | 12.6 (320) | 16 (7.3)                |
| 11962-X18                       | 41U               | 19"EIA | 18 (457) | 76.4 (1941)            | 22.4 (569) | 18.6 (472) | 20 (9.1)                |
| 11963-X06                       | 13U               | 23"    | 6 (150)  | 27.4 (696)             | 26.4 (671) | 6.6 (168)  | 10 (4.5)                |
| 11963-X12                       | 13U               | 23"    | 12 (300) | 27.4 (696)             | 26.4 (671) | 12.6 (320) | 11 (5.0)                |
| 11963-X18                       | 13U               | 23"    | 18 (457) | 27.4 (696)             | 26.4 (671) | 18.6 (472) | 13 (5.9)                |
| 11964-X06                       | 21U               | 23"    | 6 (150)  | 41.4 (1052)            | 26.4 (671) | 6.6 (168)  | 11 (5.0)                |
| 11964-X12                       | 21U               | 23"    | 12 (300) | 41.4 (1052)            | 26.4 (671) | 12.6 (320) | 12 (5.4)                |
| 11964-X18                       | 21U               | 23"    | 18 (457) | 41.4 (1052)            | 26.4 (671) | 18.6 (472) | 15 (6.8)                |
| 11965-X06                       | 41U               | 23"    | 6 (150)  | 76.4 (1941)            | 26.4 (671) | 6.6 (168)  | 16 (7.3)                |
| 11965-X12                       | 41U               | 23"    | 12 (300) | 76.4 (1941)            | 26.4 (671) | 12.6 (320) | 17 (7.7)                |
| 11965-X18                       | 41U               | 23"    | 18 (457) | 76.4 (1941)            | 26.4 (671) | 18.6 (472) | 19 (8.6)                |

X=Color: 1=Gray, 2=Computer Beige, 5=Clear, 7=Black, E=Glacier White.

800-834-4969 in U.S. & Canada • www.chatsworth.com



CHATSWORTH PRODUCTS

While every effort has been made to ensure the accuracy of all information, CPI does not accept liability for any errors or omissions and reserves the right to change information and descriptions of listed services and products.

©2015 Chatsworth Products, Inc. All rights reserved. Chatsworth Products, CPI, CPI Passive Cooling, eConnect, MegaFrame, Saf-T-Grip, Seismic Frame, SlimFrame, TeraFrame, GlobalFrame, Cube-iT Plus, Evolution, OnTrac, QuadraRack and Velocity are federally registered trademarks of Chatsworth Products. Simply Efficient is a trademark of Chatsworth Products. All other trademarks belong to their respective companies. 02/15