


# Product Information Sheet

## ADJUSTABLE BRACING KIT FOR DATACOM CABINETS

Attach bracing kit to cabinet top panel where there is a risk of seismic activity. Earthquake design criteria specify that equipment remain operational when subjected to earthquakes even though some small amount of repairable secondary physical damage may occur.

- Adjustable 24" to 36" (610 mm to 910 mm) distance from wall
- For use with M-Series, E-Series and Seismic Frame® Cabinets



Part Number		Shipping Weight		Color
19"	23"	19"	23"	
12477-119	12477-123	6 lb (2.7 kg)	7 lb (3.2 kg)	Gray
12477-219	12477-223	6 lb (2.7 kg)	7 lb (3.2 kg)	White
12477-719	12477-723	6 lb (2.7 kg)	7 lb (3.2 kg)	Black

*Note: For secure bracing, attached the cabinet to the floor using the proper floor installation kit along with CPI floor Anchor Clamp provided with each cabinet.*

800-834-4969 in U.S. & Canada • [www.chatsworth.com](http://www.chatsworth.com)



**CHATSWORTH PRODUCTS, INC.**

©2009 Chatsworth Products, Inc. All rights reserved. CPI, CPI Passive Cooling, Saf-T-Grip, Seismic Frame, SlimFrame and MegaFrame are federally registered trademarks of Chatsworth Products, Inc. Cube-iT Plus, Evolution, OnTrac, QuadraRack, Simply Efficient and TeraFrame are trademarks of Chatsworth Products, Inc. All other trademarks belong to their respective companies. 05/09