


Product Cut Sheet

2" (50 MM) DIAMETER FIBER MANAGEMENT SPOOLS

Use the 2" (50 mm) Diameter Fiber Management Spool to support fiber and copper cables within CPI's extensive line of vertical cabling sections. The spools meet EIA/TIA bend radius requirements and minimize cable tangles and tears for more efficient data transmission.

- Provides proper cable support and bend radius for more efficient data transmission
- Maintains strength under heavy cable loads
- Mounts to all CPI vertical cabling sections 6"W (150 mm) or wider, including MCS, MCS-EFX, CCS, CCS-EFX, VCS and GVCS



Part Number	Application	Package Of	Shipping Weight
12765-X02	For GVCS	2	2 lb (0.9 kg)
12765-X06	For GVCS	6	3 lb (1.4 kg)
12766-X02	For 6"W, 10"W or 12"W (150 mm, 250 mm or 300 mm) Double-Sided Cabling Sections	2	2 lb (0.9 kg)
12766-X07	For 6"W, 10"W or 12"W (150 mm, 250 mm or 300 mm) Double-Sided Cabling Sections	7	5 lb (2.3 kg)

X=color: 1=Gray, 2=Computer Beige, 5=Clear, 7=Black, E=Glacier White.

800-834-4969 in U.S. & Canada • www.chatsworth.com



©2013 Chatsworth Products, Inc. All rights reserved. CPI, CPI Passive Cooling, GlobalFrame, MegaFrame, Saf-T-Grip, Seismic Frame, SlimFrame, TeraFrame, Cube-IT Plus, Evolution, OnTrac, Velocity and QuadraRack are federally registered trademarks of Chatsworth Products. eConnect and Simply Efficient are trademarks of Chatsworth Products. All other trademarks belong to their respective companies. 07/13