

# Product Information Sheet

## CONCRETE FLOOR ANCHOR KIT FOR SEISMIC FRAME® TWO-POST RACK

Attach Seismic Frame® Two-Post Rack to a concrete slab floor with this kit of four heavy-duty anchors. The Seismic Frame® Two-Post Rack is designed specifically to support network equipment in areas with seismic activity. The welded, steel Seismic Frame Two-Post Rack resists the swaying motion caused by earthquakes to reduce the amount of vibration transferred through the rack to equipment and is less likely to be damaged during a seismic event, which means faster network recovery.

- Includes four M12 x 5-1/8" Hilti HSL-3-G Heavy Duty Sleeve Anchors
- Each rack must be secured to the structural floor
- When bayed in a continuous row, the spacing between racks should be determined by a licensed structural engineer familiar with seismic applications and code in the area. Each installation requirement varies.
- Minimum recommended thickness of the concrete slab on the ground floor is 5-1/2" (140 mm)



Part Number	Description	Shipping Weight
13702-001	Concrete Floor Anchor Kit	3 lb (1.4 kg)

*Zinc-plated finish.*

800-834-4969 in U.S. & Canada • [www.chatsworth.com](http://www.chatsworth.com)



CHATSWORTH PRODUCTS, INC.

©2009 Chatsworth Products, Inc. All rights reserved. CPI, CPI Passive Cooling, Saf-T-Grip, Seismic Frame, SlimFrame and MegaFrame are federally registered trademarks of Chatsworth Products, Inc. Cube-iT Plus, Evolution, OnTrac, QuadraRack, Simply Efficient and TeraFrame are trademarks of Chatsworth Products, Inc. All other trademarks belong to their respective companies Rev.2 03/09