

Product Information Sheet



CABLE RUNWAY GROUND STRAP KIT

Cable Runway Ground Strap Kits provide a ground pathway between cable runway lengths when fastened together across splices. Installation requires drilling 5/16" holes. Ground Straps consist of an 8" L (200 mm) #6 AWG stranded copper conductor insulated green with a horizontal yellow stripe attached at both ends to two-hole compression lugs with 1/4" bolt holes spaced on 5/8" (15.88 mm) centers.


- Overall length of 11" (280 mm)
- Available individually or in packages of 25
- Constructed of UL Listed components
- Replaces CPI P/N 12061-001
- Other configurations available on request

Kit consists of:

- (4) stainless steel cap screws, #1/4-20 x 3/4" L
- (4) flat washers, 1/4"
- (4) lock washers, 1/4"
- (4) nuts, 1/4"



Shown mounted across runway splice point



Part Number	Description	Unit	Shipping Weight lb (kg)
40164-001	#6 AWG Ground Strap	1	1 (0.5)
40164-025	#6 AWG Ground Strap	25	12 (5.0)

800-834-4969 in U.S. & Canada • www.chatsworth.com



CHATSWORTH PRODUCTS, INC.

©2010 Chatsworth Products, Inc. All rights reserved. CPI, CPI Passive Cooling, MegaFrame, Saf-T-Grip, Seismic Frame, SlimFrame and TeraFrame are federally registered trademarks of Chatsworth Products, Inc. Cube-iT Plus, Evolution, OnTrac, QuadraRack, Simply Efficient and Velocity are trademarks of Chatsworth Products, Inc. All other trademarks belong to their respective companies. 10/10