

Product Information Sheet

ALUMINUM-TO-ALUMINUM OR ALUMINUM-TO-COPPER ANTIOXIDANT JOINT COMPOUND

Recommended for all aluminum-to-aluminum and aluminum-to-copper connectors, bare conductors, Busbars, insulated conductors and conduit threads.

- Oxide-inhibiting joint compound is used to improve the electrical conductivity and enhance the integrity of any grounding or bonding connection
- Good for all voltages
- Assures a high-connectivity joint by sealing out air and moisture to prevent corrosion and reformation of oxide film
- Also used as an anti-seizing thread lubricant and ensures continuity of ground on aluminum conduit threads
- Bulk packaging quantities available



8 oz



.5 oz

Part Number	Description	Size	Unit	Shipping Weight
40166-101	Antioxidant, Gray	.5 oz	1	.1 lb
40166-801	Antioxidant, Gray	8 oz	1	.5 lb
40166-150	Antioxidant, Gray	.5 oz	50	2 lb
40166-812	Antioxidant, Gray	8 oz	12	6 lb

800-834-4969 in U.S. & Canada • www.chatsworth.com



CHATSWORTH PRODUCTS, INC.

©2003 Chatsworth Products, Inc. All rights reserved. CPI is a registered trademark of Chatsworth Products, Inc. All other trademarks belong to their respective companies. 06/03