

Product Cut Sheet

UNIVERSAL RACK



- High-strength, lightweight aluminum extrusion construction
- Two top angles or top bars and heavy-duty assembly hardware for stronger rack to handle heavier loading
- 50 special #12-24 mounting screws with combination Phillips/Straight heads and pilot points to reduce cross threading and installation time
- Unique packaging inserts eliminate damage from components hitting together in the carton during shipping and handling; racks are packed unassembled in individual cartons
- Ease of assembly is enhanced through use of threaded channels; no hex nuts are required
- Universal 5/8"-5/8"-1/2" (15.9 mm-15.9 mm-12.7 mm) alternating hole pattern offers greater mounting flexibility, maximizes usable mounting space and is compatible with conventional wide 1-1/4"-1/2" (31.8 mm -12.7 mm) alternating hole patterns
- Integrated masked grounding studs on the inside of the rack channel for quick attachment to the Telecommunications Grounding System
- Available in powder coat color finishes (Gray, Computer Beige, Black, Glacier White) or grained aluminum finish (Clear)
- State-of-the-art manufacturing methods provide the best quality and fastest delivery in the industry
- Side channels have multiple mounting holes and (4) pem nuts for quick installation of cable management
- EIA Channels: C-Shaped, 1.265" x 3" (32.13 mm x 76 mm); 25" (6.4 mm) thick front/rear flanges; 17" (4.3 mm) thick web (pair)
- Base Angles: 3.5" x 6.0" x .375" (89 mm x 152 mm x 9.53 mm) thick (pair)
- Top Angles: 1.5" x 1.5" x .25" (38 mm x 38 mm x 6.4 mm) thick (pair)
- Top Angles, Flush Bolted: 1.5" x 2.0" x .25 (38 mm x 51 mm x 6.4 mm) thick
- Top Bars: 1.5" x .25" (38 mm x 6.4 mm) thick (pair)
- Panel Mounting Holes: #12-24 rolled threads in both flanges front and back
- Custom configurations and assemblies available by special order
- Assembly hardware is included
- Select models (P/N 48353-XXX, 48383-XXX) are UL Listed: File E140851; Category DUXR (US), DUXR7 (Canada) – Communications Circuit Accessory
- Weight capacity 1500 lb (680.4 kg) — weight must be evenly distributed, and rack must be properly secured to floor

Installation Hint: When mounting equipment, use #3 Phillips tip to assure maximum torque.

Channel Cross Section and Hole Pattern Standards

CPI offers EIA aluminum channel uprights on all Standard and Universal racks. All Standard and Universal racks are threaded to accept industry standard #12-24 mounting screws. Extra care is taken in that the threads are "rolled" rather than "cut" for greater strength and durability. The Universal Rack hole pattern is 5/8"-5/8"-1/2" (15.9 mm-15.9 mm-12.7 mm) and is compatible with wide 1 1/4"-1/2" (31.8 mm-12.7 mm) patterns, while offering greater flexibility.



Rack-Mount Unit (U) marks simplify equipment installation



Ground Studs located directly on rack channel



| Top Bar or Angles | |
|-------------------|---------------------------------|
| 460 | Two Top Bars |
| 463 | Two Top Angles |
| 467 | Two Top Angles, Flush Bolted |
| 483 | UL Listed (With Two Top Angles) |

| Width - in | |
|------------|----------------|
| 5 | 19 EIA Channel |
| 8 | 23 Channel |

| Mounting Holes | |
|----------------|---------------------------|
| 3 | Mounting Holes Both Sides |

| Color | |
|-------|----------------|
| 1 | Gray |
| 2 | Computer Beige |
| 5 | Clear |
| 7 | Black |
| E | Glacier White |

| Height - ft (m) | | |
|-----------------|-----------|-----|
| 31 | 3 (0.9) | 17U |
| 20 | 4 (1.2) | 24U |
| 19 | 5 (1.5) | 31U |
| 00 | 5.6 (1.7) | 34U |
| 01 | 6 (1.8) | 38U |
| 02 | 6.6 (2.0) | 41U |
| 03 | 7 (2.1) | 45U |
| 05 | 7.6 (2.3) | 48U |
| 15 | 8 (2.4) | 51U |
| 17 | 8.6 (2.6) | 55U |
| 08 | 9 (2.7) | 58U |

4XX X X - X XX

800-834-4969 in U.S. & Canada • www.chatsworth.com



CHATSWORTH PRODUCTS

©2013 Chatsworth Products, Inc. All rights reserved. CPI, CPI Passive Cooling, GlobalFrame, MegaFrame, Saf-T-Grip, Seismic Frame, SlimFrame, TeraFrame, Cube-IT Plus, Evolution, OnTrac, Velocity and QuadraRack are federally registered trademarks of Chatsworth Products. eConnect and Simply Efficient are trademarks of Chatsworth Products. All other trademarks belong to their respective companies. 6/13