

Product Information Sheet

BASIC CONSOLIDATION POINT FOR A SINGLE PATCH PANEL (19" X 1U)



The BCE-24-N is a basic consolidation enclosure designed to be located completely above drop ceilings or completely below raised floors in non-plenum areas. The enclosure requires a space that is 22" long by 16" wide and 5" deep. BCE-24-N has a removable cover which is secured with six wing nuts. BCE-24-N includes a single pair of threaded equipment mounting rails for 19" wide equipment. Rails are 1U high and pivot to provide easy access to the front and rear of patch panels. Cable tie points are located within the enclosure. Customer must order #12-24 equipment mounting screws and Saf-T-Grip® Cable Management Straps separately.

■ Equipment Support:

- One pair of rack-mount rails, 19" wide x 1U high
- Rails pivot to provide access to the front and rear of patch panels

■ Materials

- Enclosure: .060" thick sheet aluminum, riveted construction

■ Packaging

- 1 Enclosure/Carton

■ Approvals

- UL Listed - Communications Circuit Accessory
- UL File Number/E185147 (UL 1863; UL 50; UL 2043)

■ Specifications

- Enclosure: 14-3/4" wide x 21-1/4" long x 3-1/2" deep
- Weight: 7 lb

■ Installation

- Customer provides method and hardware for ceiling or raised floor attachment.
- Order #12-24 equipment mounting screws separately (P/N 40605-001).
- Use Saf-T-Grip Cable Management Straps to secure cables (P/N 02006-201).



Part Number	Description	Shipping Weight
BCE-24-N	BCE Enclosure, 19" x 1U, Non-Plenum	7 lb

800-834-4969 US & Canada • www.chatsworth.com



CHATSWORTH PRODUCTS, INC.

©2003 Chatsworth Products, Inc. All rights reserved. CPI is a registered trademark of Chatsworth Products, Inc. All other trademarks belong to their respective companies 04/03