

©2017 Chatsworth Products. Inc.

All products quoted are subject to availability based on manufacturing capacity and shipping dates should be considered estimates only.

While every effort has been made to ensure the accuracy of all information, CPI does not accept liability for any errors or omissions and reserves the right to change information and descriptions of listed services and products.



CHATSWORTH PRODUCTS, INC.

120/208VAC, Three Phase, 50/60 Hz

16A Max Unbalanced/13.8A Balanced

NEMA L21-30, 10 ft (3m)

30A derated to 24A (NA)

CB1,CB2,CB3: (12) C-13

Locking Receptacles

(3) 2-pole 20A UL489 Breakers

Multiple tool-less mounting button

UL & cUL Listed, IEC 60950-1, CSA C22.2, CE, NOM, RoHS, FCC Part 15

locations, A and B (see detail)

208VAC, 50/60 Hz

24A per Phase

C13: 12A max

(36) C13

2.2 [55]

18 [8.2]

5 - 95%

5 - 95%

Class A, EN 55022

32 - 149F (0 - 65C)

0-10000 ft (0-3000 m)

-13 - 149F (-25 - 65C)

0-50000ft (0-15000 m)

(1) ground kit cable

(2) tool less mounting buttons

70.5 [1791] 2.2 [55]

Nominal Voltage (VAC)

Input Plug / Cord Current Rating

Power Rating (kW)

Nominal Voltage (VAC)

Max Current per Breaker

Output Ratings

Current Rating

Outlet Combination

Surge Suppression

Cord Retention

Width (In[mm]) Height (ln[mm])

Depth (ln[mm])

Weight (lbs[kg])

Operating Temperature

Operating Rel Humidity

Operating Elevation

Storage Temperature

Storage Rel Humidity

Storage Elevation

Mounting System

Load Segment

PDU Total

Features:

Outlet Rating

eConnect Vertical (0U) PDU, Basic, L21-30 Plug, Three Phase WYE, 120/208V Input, 30A, (36) C13 Outlets, 208V Output

THIRD ANGLE

1 All Dimension are in inches [millimeters] unless otherwise specified

2 Installation must conform with all related national and local codes

3 All Bracket kits are sold separately. Toolless mounting buttons are included for installation in CPI cabinets.

4 For more information, please contact Tech Support at techsupport@chatsworth.com