

2 Installation must conform with all related national and local codes

3 All Bracket kits are sold separately. Toolless mounting buttons are included for installation in CPI cabinets.

4 For more information, please contact Tech Support at techsupport@chatsworth.com

Technical Specs: Input Ratings 220-240VAC, Single Phase, 50/60 Hz Nominal Voltage (VAC) Input Plug / Cord IEC 32A 2P+E, 10 ft (3m) 32A Total Current Rating 7.3 (@230V) Power Rating (kW) Output Ratings 220-240VAC, 50/60 Hz Nominal Voltage (VAC) Current Rating 32A Total C13: 12A max Outlet Rating 16A Max Max Current per Breaker Outlet Combination CB1,CB2: (18) C-13 Load Segment PDU Total (36) C13 Branch Circuit Protection (2) 2-pole 16A UL489 Breakers Surge Suppression None Features: (1) LCD Display - Branch Monitoring, IP Local Display Setup, Alarm Notification Current, Voltage, Power, Branch Monitoring PF per Circuit Monitoring Accuracy +/- 1% True RMS 10/100/1000 Mbps RJ-45 Ethernet Port IP v4/v6, SNMP v1/v2/v3, Serial Remote Monitoring Link up to 32 PDUs under a single IP Consolidation IP address Update firmware USB Port Built-in Web Browser, HTTP, Control Interface SNMP, Serial RS-232 Sensor Interface (2) Temperature and Humidity Sensors Front and Rear Electric Door Lock Auxiliary Ports (2) Cord Retention Locking Receptacles Multiple tool-less mounting button Mounting System locations. A and B (see detail) Dimensions & Weights: 2.2 [55] Width (In[mm]) 70.5 [1791] Height (In[mm]) 2.2 [55] Depth (In[mm]) 18 [8.2] Weight (lbs[kg]) UL & cUL Listed, IEC 60950-1, CSA **Regulatory Information:** C22.2, CE, NOM, RoHS, FCC Part 15 Class A, EN 55022 **Environmental Conditions:** Operating Temperature 32 - 149F (0 - 65C) 5 - 95% Operating Rel Humidity **Operating Elevation** 0-10000 ft (0-3000 m) -13 - 149F (-25 - 65C) Storage Temperature 5 - 95% Storage Rel Humidity 0-50000ft (0-15000 m) Storage Elevation (2) tool less mounting buttons Hardware Included: (1) ground kit cable Temp/Hum Environmental Sensor Optional Accessories: P/N 35941-132

ensure the accuracy of all information, errors or omissions and reserves the right to change information and descriptions of listed services and products.



CHATSWORTH PRODUCTS, INC.

eConnect Vertical (0U) PDU, Monitored, IEC 32A 2P+E Plug, Single Pháse, 220-240V Input, 32A, (36) C13 Outlets, 220-240V Output

